

BEFORE THE ENVIRONMENTAL QUALITY COUNCIL  
STATE OF WYOMING

In the Matter of the Appeal )  
And Petition for Hearing of: )  
Croell Redi-Mix, DEQ AQD Permit ) Docket No. 10-2803  
Application No. AP-9645 )  
And DEQ AQD Permit No. MD-9645 )  
Dated March 17, 2010 )

---

**DEQ'S MOTION FOR SUMMARY JUDGMENT**

**EXHIBIT 24**

---

File Memo

DEQ Bates Nos. 000106

## Memorandum

**To:** File -AP-9645  
**From:** Nick Meeker  
**Date:** March 15, 2010  
**Re:** Changes to Permit Conditions

The Division added the following conditions to Air Quality Permit MD-9645:

- The amount of limestone crushed or hauled from the quarry shall not exceed 500,000 tons per year. Records shall be kept for a period of five (5) years to demonstrate compliance with this condition and shall be made available to the Division upon request.
- Croell Redi-Mix, Inc. shall stabilize the exposed areas against wind erosion at the quarry. Newly disturbed areas shall be treated within sixty (60) days of completion of stripping unless otherwise approved by the Division. Reclamation areas shall be stabilized against wind erosion within sixty (60) days of reaching the approved post mining topography, unless otherwise approved by the Division. Stabilization practices may consist of ripping or chiseling to create a roughened surface, seeding with a temporary vegetative cover or other practices which effectively stabilize against wind erosion. Localized areas identified for equipment storage/staging, work areas and required buffers for haul roads and reclamation are not required to be stabilized.
- That all work areas, disturbed areas and stockpiles shall be treated with water and/or chemical dust suppressants on a schedule sufficient to control fugitive dust. At a minimum, two (2) applications of chemical dust suppressant shall be applied annually to all work areas in accordance with the manufacturer's recommendations. The chemical dust suppressant shall be maintained continuously to the extent that it remains a viable control measure, which may require additional applications. All work areas shall receive an initial treatment of chemical dust suppressant prior to any activities at the beginning of each construction season.